

Landini

Compact

2840 | 3640 | 4740

Agricultural



Turf



4740H Industrial



Landini
DIVISION OF ARGO INDUSTRIAL (PTY) LTD

SPECIFICATIONS

MODEL	2840/H	3640/H	4740/H
ENGINE: MAKE: MODEL:	Mitsubishi S4L	Mitsubishi S4L2	Mitsubishi S4QL
Gross Output (hp/kW)	28/21	38/29	47/35
Rated Speed (rpm)	2600	2700	2600
Type	Inline Indirect	Inline Indirect	Inline Indirect
No of Cylinders	4	4	4
Bore/Stroke (mm)	78x78.5	78x92	88x103
Displacement (cc)	1500	1758	2505
Air Cleaner	Dry Dual Element	Dry Dual Element	Dry Dual Element
Fuel Tank Capacity (lt)	32	32	40
Cooling System	Water-Cooled	Water-Cooled	Water-Cooled
POWER TAKE OFF (PTO)			
Type (STD) (OPT)	Independent PTO	Independent PTO	Independent PTO
Maximum Power (hp/kW)	23/17	31/23	41/31
PTO Speed std (opt) (rpm)	540	540	540
Safety Interlock Control	Yes Electro Hydraulic	Yes Electro Hydraulic	Yes Electro Hydraulic
TRANSMISSION			
Basic Transmission (OPT/ HST)	12+12	12+12	16+16
Creeper	N/A	N/A	OPT
Speed Range (Gear) (km/h)	1,7-26,1	1,7-27,4	1,08-32,4
Main Gear Shift Type	Synchro Shuttle	Synchro Shuttle	Synchro Shuttle
Range Gear Shift Type	Gear Sliding	Gear Sliding	Collar Shift
Foot operated rear Diff-lock	Mechanical	Mechanical	Mechanical
BRAKES			
Brake Type	Wet, multi disc	Wet, multi disc	Wet, multi disc
Parking Brake (hand lever)	Yes	Yes	Yes
HYDRAULICS			
Control: position-, draft-, mixed	STD	STD	STD
Delivery (lpm) Main	30	30,8	31
Steering	13	13,6	15,6
Remote valves (STD)	2	2	2
Lifting capacity at the ball end (kg)	1188	1188	1250
3-point linkage category	1	1	1
STEERING			
Type	Hydrostatic	Hydrostatic	Hydrostatic
ELECTRICALS			
Battery capacity	12V, 80AH	12V, 80AH	12V,80AH
Alternator	12V-50A	12V-50A	12V- 50A
AXLES			
Wheel base (mm)	1660	1660	1758
Turning radius with brake (mm)	2558	2558	2540
Turning radius without brake (mm)	2896	2896	2740
TYRES (Agricultural) ‡			
Standard tyres Front	7-14,4PR(6-14)	7-16,4 PR(7-14)	8-18,4 PR
Agricultural type Rear	11,2-24,8PR(9,5-24)	12,4-24,8PR(11,2-24)	13,6-24,6 PR
TYRES (Turf) ‡			
Front	25 x 8.50-14NHS	25 x 8.50-14NHS	25 x 8.50-14NHS
Rear	41 x 14.00-20NHS	41 x 14.00-20NHS	41 x 14.00-20NHS
CONFIGURATION			
ROPS	STD	STD	STD
CAB	N/A	N/A	N/A
DIMENSIONS			
Length(bumper to link end)(mm)	2987	2987	3192
Tread (mm)	1059	1059	1100
Height (mm) ROPS	2314	2353	2447
Ground clearance (mm)	330	330	387
Weight without ballast (kg) ROPS	1200	1230	1625

Key: STD = Standard | OPT = Optional | N/A = Not Available

‡ = Track adjustment not with listed tyres

See operations and maintenance manual for adjustment with specific tyres

**ONDERWORPE AAN VERANDERING SONDER KENNISGEWING
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE**



DIVISION OF ARGO INDUSTRIAL (PTY) LTD