

Landini

POWERMaster T₃

190 | 210 | 230




ARGO Industrial (Pty) Ltd

SPECIFICATIONS

MODEL	190	210	230
ENGINE			
	β-Power Turbo / Common Rail / Air to Air Intercooler		
Rated Power (hp/kW)	164/119	178/134	190/143
Rated speed (rpm)	2200	2200	2200
No of cylinders	6	6	6
Capacity (ℓ)	6,7	6,7	6,7
Bore/Stroke (mm)	104/132	104/132	104/132
Number of valves	24	24	24
Max. torque (Nm)	747	800	850
Max. torque (rpm)	1400	1400	1400
Torque rise (%)	40	38	37
Fuel tank capacity (lt.)	350	350	350
TRANSMISSION			
Landini E/E Plus version Xtra Shift (32 Fwd. + 24 Rev.)	•	•	•
Electro-Hydraulic shifting with reverse power shuttle			
Auto Speed matching			
Max. road speed - 40 km/h	•	•	•
Creeper	OPT	OPT	OPT
FOUR WHEEL DRIVE			
Differential Lock (Hydraulic)	•	•	•
Rigid front axle	•	•	•
Steering angle (°)	55	55	55
POWER TAKE OFF			
Electro-Hydraulic control electrically modulated	•	•	•
Speeds 540 or 1000 rpm	•	•	•
HYDRAULIC SYSTEM			
Closed hydraulic circuit with pressure flow compensation	•	•	•
Total hydraulic flow (l/min.)	130	130	130
Max. lift capacity (kg)	10950	10950	10950
Category type	II & III	II & III	II & III
WEIGHTS, DIMENSIONS AND TYRES			
Total weight without ballast (kg)	7250	7250	7250
Wheelbase (mm)	2873	2873	2873
Overall length with front weights (mm)	5500	5500	5500
Height over cab (mm)	3000	3000	3000
Tyres Front	540/65R30	540/65R30	540/65R30
Tyres Rear	650/65R42	650/65R42	650/65R42
Track adjustment (mm)	1720min.-2030 max	1720min.-2030 max	1720min.-2030 max

Key: • = Standard | OPT = Optional | – = Not Available

ONDERWORPE AAN VERANDERING SONDER KENNISGEWING
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE