

Landini

Rex Techno

60F | 75F | 85F



Landini
DIVISION OF ARGON INDUSTRIAL (PTY) LTD

SPECIFICATIONS

| MODEL | 60F | 75F | 85F |
|---|----------|-----------|-----------|
| ENGINE | | | |
| Direct Injection Perkins Engine | 1103C-33 | 1104C-44 | 1104C-44 |
| Max. Power ISO (hp/kW) | 59/43 | 68/51 | 82/60 |
| Max Torque (Nm) | 222 | 273 | 292 |
| Max. Torque Speed (rpm) | 1400 | 1400 | 1400 |
| Displacement/Nr. of cylinders (cm ³) | 3300/3 | 4400/4 | 4400/4 |
| Fuel Tank Capacity (Aux Tank) (lt) | 48 | 48 (25) | 48 (25) |
| CLUTCH UNIT | | | |
| Independent Dry Dual Clutch (inch) | 11 | 12 | 12 |
| Mechanical Operated | STD | STD | STD |
| TRANSMISSION | | | |
| 12Fwd + 12 Rev. + shuttle | STD | STD | STD |
| POWER TAKE OFF (PTO) | | | |
| Mechanical Engagement | STD | STD | STD |
| 2 Speeds 540/540E with groundspeed (rpm) | STD | STD | STD |
| 4WD FRONT AXLE | | | |
| 4 WD Mechanical Engagement (No brakes) | STD | STD | STD |
| Max. steering angle (°) | 50 | 50 | 50 |
| Limited slip front differential | STD | STD | STD |
| HYDRAULIC POWER LIFT | | | |
| Functions: position-, draft-, intermix-, and floating control functions | STD | STD | STD |
| Standard lifting power (kg) | 2600 | 2600 | 2600 |
| Hydraulic pump delivery (lters/min) (Power Lift + Steering) | 53 + 30 | 53 + 30 | 53 + 30 |
| Cat.II 3 point linkage | STD | STD | STD |
| Standard auxiliary valves | 2 | 2 | 2 |
| TYRES AND WHEELS ‡ | | | |
| 2WD Front | 6.00x16 | 6.00x16 | 6.00x16 |
| 4WD Front | 8.25-16 | 280/70R16 | 280/70R16 |
| Rear. 2WD and 4WD | 13.6R24 | 14.9R24 | 14.9R24 |
| WEIGHTS AND DIMENSIONS (IN RUNNING ORDER) | | | |
| A. Length 2WD / 4WD (mm) | 3600 | 3709 | 3709 |
| B. Min. width (Fenders) (mm) | 1249 | 1249 | 1249 |
| C. Wheelbase 2WD (mm) | 2065 | 2174 | 2174 |
| C. Wheelbase 4WD (mm) | 2017 | 2134 | 2134 |
| D. Height at steering wheel (mm) | 1450 | 1450 | 1450 |
| E. Max ground clearance (mm) | 380 | 380 | 380 |
| F. Height to ROPS (mm) | 2186 | 2186 | 2186 |
| Weight 2WD (kg) (Without ballast) | 2500 | 2615 | 2615 |
| Weight 4WD (kg) (Without ballast) | 2675 | 2845 | 284 |

Key: STD = Standard | OPT = Optional | N/A = Not Available

* = Power estimated by the manufacturer

‡ = Track adjustment not with listed tyres

See operations and maintenance manual for adjustment with specific tyres

**ONDERWORPE AAN VERANDERING SONDER KENNISGEWING
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE**

Landini

DIVISION OF ARGO INDUSTRIAL (PTY) LTD