

Landini

Trekker

Compact | Fruit | Standard

60 / 70

75 / 85 / 95 / 105

85 / 95 / 105



Compact



Fruit



Standard



Landini
DIVISION OF ARGO INDUSTRIAL (PTY) LTD

SPECIFICATIONS

MODEL: COMPACT

60F

70F

ENGINE

Euro2/TIER2 Perkins	4TNV94L-NLAN	4TNV98L-NLAN
Max Power ISO (hp/kW)	59 / 43	70 / 51
Rated speed (rpm)	2500	2500
Max Torque (Nm)	205	245
Max Torque Speed (rpm)	1100	1100
Displacement/Nr. of cylinders (cm ³)	3054/4	3318/4

TRANSMISSION

Basic gearbox+underdrive+rev. shuttle 16FWD+8REV	STD	STD
Basic gearbox+creeper+rev. shuttle 16FWD+8REV	OPT	OPT

POWER TAKE OFF (PTO)

2 Speeds 540/750 (rpm)	STD	STD
------------------------	-----	-----

STEERING SYSTEM

HI-DRIVE hydrostatic steering	STD	STD
-------------------------------	-----	-----

BRAKES

Oil-immersed multi-disc graphite brakes	STD	STD
---	-----	-----

HYDRAULIC POWER LIFT

Standard lifting power (kg)	2000	2000
-----------------------------	------	------

TRACKS

Track frame with 5 lower guide rollers and one upper	STD	STD
--	-----	-----

WEIGHTS AND DIMENSIONS

Max length narrow / STD (mm)	3100 / 3100	3100 / 3100
Min width Narrow / STD (mm)	1130 / 1336	1130 / 1336

DOZER BLADE*

	OPT	OPT
--	-----	-----

MODEL: FRUIT

75F

85F

95F

105F

ENGINE

Euro2/TIER2 Perkins	1104C-44	1104C-44	1104C-44T	1104C-44T
Max Power ISO (hp/kW)	68/50	81/60	91/67	98/72
Rated speed (rpm)	2500	2500	2500	2500
Max Torque (Nm)	201	215	280	268
Max Torque Speed (rpm)	1100	1100	1100	1100
Displacement/Nr. of cylinders (cm ³)	4400/4	4400/4	4400/4	4400/4

TRANSMISSION

Basic gearbox+underdrive+rev. shuttle 16FWD+8REV	STD	STD	STD	STD
--	-----	-----	-----	-----

POWER TAKE OFF (PTO)

Hydraulic Engagement	STD	STD	STD	STD
2 Speeds 540/750 (rpm)	STD	STD	STD	STD

STEERING SYSTEM

HI-DRIVE hydrostatic steering	STD	STD	STD	STD
-------------------------------	-----	-----	-----	-----

BRAKES

Oil-immersed multi-disc graphite brakes	STD	STD	STD	STD
---	-----	-----	-----	-----

HYDRAULIC POWER LIFT

Standard lifting power (kg)	2650	2650	2650	2650
-----------------------------	------	------	------	------

TRACKS

Track frame with 5 lower guide rollers and one upper	STD		STD	
--	-----	--	-----	--

WEIGHTS AND DIMENSIONS

Max length	3500	3500	3500	3500
Min width Narrow / STD (mm)	1460 / 1660	1460/1660	1460/1670	1460/1700

DOZER BLADE*

	OPT	OPT	OPT	OPT
--	-----	-----	-----	-----

MODEL: STANDARD

85F

95F

105F

ENGINE

Euro2/TIER2 Perkins	1104C-44	1104-44T	1104-44T
Max Power ISO (hp/kW)	81/60	91/67	98/72
Rated speed (rpm)	2500	2500	2500
Max Torque (Nm)	215	280	268
Max Torque Speed (rpm)	1100	1100	1100
Displacement/Nr. of cylinders (cm ³)	4400/4	4400/4	4400

TRANSMISSION

Basic gearbox+underdrive+rev. shuttle 16FWD+8REV	STD	STD	STD
Basic gearbox+creeper+rev. shuttle 16FWD+8REV	OPT	OPT	OPT

POWER TAKE OFF (PTO)

Hydraulic Engagement	STD	STD	STD
2 Speeds 540/750 (rpm)	STD	STD	STD

STEERING SYSTEM

HI-DRIVE hydrostatic steering	STD	STD	STD
-------------------------------	-----	-----	-----

BRAKES

Oil-immersed multi-disc graphite brakes	STD	STD	STD
---	-----	-----	-----

HYDRAULIC POWER LIFT

Standard lifting power (kg)	2650	2650	2650
-----------------------------	------	------	------

TRACKS

Track frame with 5 lower guide rollers and one upper	STD	STD	STD
--	-----	-----	-----

WEIGHTS AND DIMENSIONS

Max length (mm)	3500	3500	3500
Min width (mm)	1700	1750	1750

DOZER BLADE*

	OPT	OPT	OPT
--	-----	-----	-----

Key: STD = Standard | OPT = Optional | N/A = Not Available

* = Note: Dozer Blade less front weights

ONDERWORPE AAN VERANDERING SONDER KENNISGEWING
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

Landini

DIVISION OF ARGO INDUSTRIAL (PTY) LTD