

SPECIFICATION

MODEL

Technofarm 60

Technofarm 75

ENGINE

Direct injection Perkins engine	1103C-33	1104C-44
Rated power (hp/kW)	58/43	68/50
Rated speed (rpm)	2200	2200
Max torque (Nm)	222	273
Max torque speed (rpm)	1400	1400
Bore/Stroke (mm)	105/127	105/127
Displacement/Nr. of cylinders (cm ³)	3300/3	4400/4
Compression ratio	19.25:1	19.3:1
Water cooling	STD	STD
Air filter	STD	STD
Fuel tank capacity (lt)	65	65

CLUTCH UNIT

Independent dry dual clutch (inch)	11	12
Mechanical engagement	STD	STD

TRANSMISSION

Speed Four + Rev. shuttle: 12Fwd + 12Rev	STD	STD
Mechanical Reverse Shuttle	STD	STD
Rear mechanical diff-lock	STD	STD

POWER TAKE OFF (PTO)

Mechanical engagement	STD	STD
Speeds 540/540E (rpm) With Ground Speed	STD	STD
1 3/8 (34,9 mm) PTO shaft with splines	STD	STD

4WD FRONT AXLE

Mechanical 4WD Engagement	STD	STD
4WD max. Steering Angle (°)	55	55
2WD max Steering Angle (°)	56	56

BRAKES

Mechanical braking System, Oil-bath graphite coated rear brakes - 10 discs	STD	STD
--	-----	-----

HYDRAULIC POWER LIFT

Functions: position-, draft-, intermix-, and floating controls	STD	STD
Mechanical Operated	STD	STD
Max. lifting power (kg)	2700	2700
Hydraulic pump delivery (ltr/min)	42	42
Cat II three-piont linkage	STD	STD
Standard auxiliary valves STD/OPT	1/2	1/2

WEIGHTS AND DIMENSIONS (IN RUNNING ORDER)

Front tyres 2WD	7.50-16	7.50X16
Front tyres 4WD	11.2R20	360/70R20
Rear tyres 2WD	14.9-R28	420/70R30
Rear tyres 4WD	14.9R28	420/70R30
Total length with ballast (mm)	3873	3990
Height at steering wheel (mm)	1585	1585
Min width (mm)	1690	1790
Max ground clearance (mm)	367	367
Height to ROPS (mm)	2410	2410
Min turning radius (with brakes) (mm)	3500	3500
Weight 2WD without ballast (kg)	2354	2454
Weight 4WD without ballast (kg)	2484	2584

TRACK

Front track adjustment 4WD# (mm)	1410-1886	1450-1846
Rear track adjustment # (mm)	1190-1907	1194-1905

OPTIONAL EQUIPMENT

Front ballast of 36 kg each 2WD/4WD	6 x STD	6 x STD
Rear ballast of 45 kg each	2 x STD	2 x STD

Key: STD = Standard | OPT = Optional | — = Not Available

* = Power estimated by the manufacturer

‡ = Track adjustment not with listed tyres

See operations and maintenance manual for adjustment with specific tyres

ONDERWORPE AAN VERANDERING SONDER KENNISGEWING
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE