

McCORMICK

BOORD REEKS ORCHARD RANGE

60F / 75F / 85F | Techno



SPECIFICATIONS

MODEL	60F TECHNO	75F TECHNO	85F TECHNO
ENGINE			
Direct Injection Perkins Engine	1103C-33	1104C-44	1104C-44
Max Power ISO (hp/kW)	59/43	68/51	82/60
Max Torque (Nm)	222	273	292
Max Torque Speed (rpm)	1400	1400	1400
Displacement/Nr of cylinders (cm ³)	3300/3	4400/4	4400/4
Fuel Tank Capacity (Aux. Tank) (lt)	48	48 (25)	48 (25)
CLUTCH UNIT			
Independent Dry Dual Clutch (inch)	11	12	12
Mechanical Operated	STD	STD	STD
TRANSMISSION			
12Fwd + 12 Rev. + shuttle	STD	STD	STD
POWER TAKE OFF (PTO)			
Mechanical Engagement	STD	STD	STD
2 Speeds 540/540E with groundspeed (rpm)	STD	STD	STD
4WD FRONT AXLE			
4 WD Mechanical Engagement (No brakes)	STD	STD	STD
Max steering angle (°)	50	50	50
Limited slip front differential	STD	STD	STD
HYDRAULIC POWER LIFT			
Functions: position-, draft-, intermix-, and floating control functions	STD	STD	STD
Standard lifting power (kg)	2600	2600	2600
Hydraulic pump delivery (lters/min) (Power Lift + Steering)	53 + 30	53 + 30	53 + 30
Cat II 3 point linkage	STD	STD	STD
Standard auxiliary valves	2	2	2
TYRES AND WHEELS			
2WD Front	6.00x16	6.00x16	6.00x16
4WD Front	8.25-16	280/70R16	280/70R16
Rear 2WD and 4WD	13.6R24	14.9R24	14.9R24
WEIGHTS AND DIMENSIONS (IN RUNNING ORDER)			
A. Length 2WD / 4WD (mm)	3600	3709	3709
B. Min. width (Fenders) (mm)	1249	1249	1249
C. Wheelbase 2WD (mm)	2065	2174	2174
C. Wheelbase 4WD (mm)	2017	2134	2134
D. Height at steering wheel (mm)	1450	1450	1450
E. Max ground clearance (mm)	380	380	380
F. Height to ROPS (mm)	2186	2186	2186
Weight 2WD (kg) (Without ballast)	2500	2615	2615
Weight 4WD (kg) (Without ballast)	2675	2845	2845

Key: STD = Standard | OPT = Optional | - = Not Available

*Power estimated by the manufacturer

‡ = Track adjustment not with listed tyres

See operations and maintenance manual for adjustment with specific tyres

ONDERWORPE AAN VERANDERING SONDER KENNISGEWING
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE